

Data Sheet

SAFECURE SEALER

Water Based Concrete Curing & Sealing Compound



DESCRIPTION

SAFECURE SEALER is a water based, low odour, membrane forming liquid for curing, sealing and dustproofing concrete. SAFECURE SEALER is suitable for use over new and old concrete and performs well on both interior and exterior concrete.

SAFECURE SEALER is a white, opaque liquid. After application and drying, the film is clear with a slight glossy appearance. Heavy applications and/or prolonged exposure to moisture will cause the cured film to have a milky appearance. Drying will allow the sealer to become clear again.

BENEFITS

- Forms an efficient moisture barrier for optimum curing of concrete
- Seals concrete surfaces to protect against the effects of weathering
- Hardens concrete surfaces by promoting proper cement hydration
- Helps eliminate dusting through good strength development
- Dries to a clear transparent film that resists yellowing under exterior or ultraviolet exposure (see Precautions/Limitations)
- Gives an alternative to solvent based materials where fumes may be objectionable, undesirable, or noncompliant

SPECIFICATIONS / COMPLIANCES

- SI 2773 VOC in Paints Varnishes etc
- ASTM C-309, Type 1, Class A & B
- AASHTO M-148, Type 1, Class B
- This product meets all air quality standards for California, New Jersey and locales with similar clean air restrictions
- U.S.D.A. approved for use in facilities where this sealer may come into incidental contact with food products.
- This product meets V.O.C. contents in accordance to EPA 40 CFR Part 59 Table 1 Subpart D for Concrete Curing Compounds with a maximum V.O.C. content of 700 g/l

INSTRUCTIONS FOR USE

Surface Preparation - The concrete surface must be clean and free of standing water. Remove any sealer or other material that may prevent adhesion of the SAFECURE SEALER.

Mixing - SAFECURE SEALER requires no preblending and should be used directly from the container.

Application - Apply at a uniform coverage by spray or roller application. Product may be sprayed with a hand held "pump-up" sprayer or with an airless industrial sprayer. If roller applied, use a short 8-10mm. nap sleeve.

Curing - For the best cure of freshly placed concrete, apply SAFECURE SEALER as soon as possible after finishing operations and/or immediately after the disappearance of the "sheen" of surface moisture.

Sealing - When sealing old concrete, remove contaminants and stains such as waxes, grease and oil with strong soaps or caustics rather than acids. **The surface must be clean and dampened with water prior to application; however, any standing water should be removed.**

Apply SAFECURE SEALER at recommended coverage rates. If a second coat is desired, apply within 2-4 hours of the previous coat.

SPRAYER CLEANING

Immediately after spraying, clean line and nozzle thoroughly with water.

Lea Road, Trading Estate, Waltham Abbey, Essex EN9 1AE
Tel: 01992 710 684 Fax: 01992 712 813
Email: sales@adomast.co.uk Website: <http://www.adomast.co.uk>

ABCD ### Issue: #
Issued: Month Year

