



FLOOR and WALL SEAL

DESCRIPTION. Kingfisher FLOOR & WALL SEAL is a very fine particle pure acrylic dispersion, formulated to provide an economic yet tough floor and wall coating / sealer.

USES. The product is designed to prevent dusting on concrete floor surfaces, both internally and externally and to protect concrete, stone, quarry tiles, thermoplastic tiles, timber etc. against water ingress and subsequent frost attack as well as staining from petrol, oil and many household chemicals

MAIN AREAS of USE

1. Domestic, commercial and industrial concrete floors,
2. Coating of internal and external friable walls prior to decoration.

ADVANTAGES.

- Easy to use – straight from the can.
- Solvent free.
- Produces a colourless, sealed, non dusting finish.
- Tough finish which gives resistance to abrasion from pedestrian and light vehicle traffic.
- Tools can be cleaned with soap and water after use.

NOTE: Kingfisher FLOOR & WALL SEAL will not "make good" floors or surfaces where prior disintegration has taken place, nor will it give added strength to these areas.

APPLICATION All substrates should be clean and free from laitance, dust, dirt, grease, fats, curing membranes etc.

The product may be applied to damp surfaces, but this will retard drying times and limit penetration, adhesion and durability.

Supplied ready to use, the product can be applied by brush, roller or spray with a coverage per coat of between 4 - 6 sq metres per coat depending on the porosity of the surface.

One coat should normally be sufficient but very porous surfaces may require additional coats.

Drying time will vary depending on the ambient temperature, but normally 4 – 8 hours should be allowed for each coat to fully dry.

For the best results allow surfaces to cure for a minimum of 24 hours before allowing traffic /pedestrian use.

DO NOT apply at air or surface temperatures below 8^o C.

PACKAGING / STORAGE / SHELF LIFE. Kingfisher FLOOR & WALL SEAL is available in 5, 25 and 200 litre plastic containers. It should be stored in a cool, dry area, AVOID frost and direct sunlight. Shelf life of the product in, unopened, sealed containers is 12 months.

CLEANING Tools and equipment should be cleaned with warm soap and water immediately after use. DO NOT allow to dry before cleaning.

HEALTH & SAFETY Wear gloves and overalls during application. If applying by spray wear face mask.

For further Health and Safety information on this product please refer to the Kingfisher Safety Data Sheet, copies of which are available from the Kingfisher Technical Dept. Tel. 01229 869100 or Fax 01229 868101.

THE INFORMATION GIVEN IN THIS DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THE COMPANY'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER NO WARRANTY, GUARANTEE OR REPRESENTATION IS MADE AS TO IT'S ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY THEMSELVES AS TO THE SUITABILITY AND APPLICATION OF SUCH INFORMATION FOR THEIR OWN USE.