

# ACM Asphalt Paint

A solvent free paint for internal and external asphalt and bitumen surfaces



**ACM Asphalt Paint** is the ideal way to seal, protect and colour asphalt and similar surfaces. The thick, flexible coating is easy to apply by brush or roller and is available in a range of attractive colours.

**ACM Asphalt Paint** is ideal for use in warehouses, plant rooms, asphalt walkways on roofs, car park bays and for line marking on tennis courts, playgrounds etc.

**Colours Available:** White, Tile Red, Green, Light Blue, Light Grey, Black

**Appearance:** Coloured, low to mid sheen finish depending upon substrate and number of coats applied.

**Coverage :** 5 litres covers 20-30m<sup>2</sup> per coat depending on the texture of the substrate. One coat normally required. The coverage rate does not allow for filling the crevices and texture of a tarmac or asphalt surface. Using the product in this way will greatly reduce coverage and extend drying time.

**Shelf Life:** At least one year in manufacturer's unopened containers.

**Storage:** Store in cool, dry conditions away from direct sunlight.

**Surface Preparation:** ACM Asphalt Paint can be applied to asphalt, tarmac, porous concrete, masonry, bricks, breeze blocks and most metals. Ensure the surface is clean, sound and dry (slightly damp is acceptable). ACM Asphalt Paint can be applied to existing paint providing all poorly bonded material is removed and glossy surfaces are dulled using abrasive paper.

**Application:** Apply ACM Asphalt Paint by brush or medium pile type roller. One coat is generally sufficient although a second coat may be required on very porous or very rough surfaces. Avoid applying too thickly. Do not apply externally if rain or frost is forecast or if the temperature is below 10°C. The second coat should be applied after approximately 1 hour.

**Curing Time:** The product will cure sufficiently in approximately 24 hours to accept light traffic, but allow 48 hours before bringing the area back into full use. Cold, damp or humid weather will delay curing.

**Cleaning of Applicators:** Clean applicators in warm soapy water before the product has started to cure.

**Health & Safety:** Contact ACM for details



Advanced  
Construction  
Materials Ltd



The Heath Business and Technical Park, Runcorn WA7 4QX

Tel: 01928 515787 Fax: 01928 515791

