



ACM Epoxy Dustproof/Sealer

Old or new concrete can be a source of dust, which is unacceptable in many manufacturing and warehouse environments. ACM Epoxy Dustproof/Sealer provides an economical and effective answer to this problem, providing a durable finish that is attractive and readily cleaned. ACM Epoxy Dustproof/Sealer is solvent free, low odour and non-tainting allowing use in food production areas, electronics factories, warehouses, engineering premises, manufacturing plants and many more.

ADVANTAGES

ACM Epoxy Dustproof/Sealer is a hard wearing, hygienic, attractive, solvent free, economical, low odour water dispersed epoxy floor coating. Adhesion is good to most clean and dry substrates. Wear resistance is excellent. Chemical resistance is good. Also useful as a priming coat under ACM Epoxicote. ACM Epoxy Dustproof/Sealer generally has a sheen finish. A matt version is available at extra cost.

SURFACE PREPARATION

Subfloor preparation is of key importance with products of this nature. The surface should be free of oil and grease. Weak material or laitence should be removed prior to application of the product. Highly polished surfaces e.g. powerfloated concrete, marble and terrazzo tiles should be mechanically textured. The floor should then be either vacuumed or swept clean. Sound, stable floor construction is essential.

APPLICATION PROCEDURE

Stir the contents of both components tins and thoroughly mix together. Drill spinners/paddles, spatulas or other square-edged implements are recommended for mixing. When mixed, do not leave in tin as flash set may occur. Spread onto floor or apply from tray/scuttle (available from ACM). Long pile (sheepskin type) rollers recommended (also available from ACM).

PACK SIZE / COVERAGE

5L packs, coverage approx. 30sq.m. A single coat often suffices but a two coat application provides the best resistance.



CURING

Within 24 hours at normal temperature.

COLOURS AVAILABLE

Light Grey, Mid Grey, Tile Red, Mid Blue, Mid Green, Buff, Safety Yellow, Terracotta, Black, White. Colours may be available on request including RAL and BS colours, contact ACM for details.

HEALTH AND SAFETY

Information supplied upon request.

CONTRACT APPLICATION

A network of approved independent installers is established for contract application. Please contact ACM for details.

TECHNICAL SERVICE

A full application and advisory service is available.

IMPORTANT: Splitting packs for economy reasons is risky and could lead to failure to set.



Advanced
Construction
Materials Ltd



ISO 9001 quality standard
for manufacture & supply

The Heath Business and Technical Park, Runcorn WA7 4QX Telephone: 01928 515787 Facsimile: 01928 515791 www.acml.co.uk

IMPORTANT NOTE

The information contained in this Data Sheet is based on tests believed to be reliable, practical experience and is published in good faith. However because we have no control over the application conditions we do not guarantee the results obtained. Responsibility for establishing suitability of the product rests with the purchaser. No liability or claim for damage or consequential loss is accepted from the use of this product. Whilst every effort has been made to ensure the information is correct at the time of publication it is the responsibility of the user to ensure that the product is suitable for the particular installation.

Please note that the mix design above for sand, cement and granite is for indication purposes only and does not serve as a specification. Suitability of the mix design for a particular project is down to the installer.