



Specialist Construction Supplies for Repair, Maintenance, Building & Infrastructure

## Black Jack Black Bitumen Paint Data Sheet

### Specification notes

Product: **Black Jack Black**

### Bitumen Paint

Supplier:

**Arcon Construction Supplies**  
**19-20 Prestwood Court Leacroft**  
**Road**  
**Warrington**  
**WA3 6SB**

Tel: **01925 852225**

Email: [mail@arconsupplies.co.uk](mailto:mail@arconsupplies.co.uk)

Web: [www.arconsupplies.co.uk](http://www.arconsupplies.co.uk)

Call 01925852225 or visit [Arcon Construction Supplies](http://www.arconsupplies.co.uk) website

...for technical, specification & application advice;

or

...for more information on our other repair, maintenance,  
engineering and construction specialist products.

[Industrial Flooring](#) | [Concrete Repairs](#) | [Protective and Waterproof Coatings](#)

[Jointing and Paving Mortars](#) | [Anti-slip Floor Paints](#) | [Non-shrink Grouts & Mortars](#)

**Black Jack Black Bitumen Paint Data Sheet**

**901 BLACK BITUMEN PAINT**

Colour	Product Code	Pack Size	Box Qty
Black	90101	1Ltr	12
	90102	2.5Ltr	6
	90105	5Ltr	4
	90125	25Ltr	1

**Product Description**

EVERBUILD BLACK BITUMEN PAINT is a solvent based, full bodied black bitumen paint, When dry, the product forms an odourless and taint free bitumen film suitable for the protection of metals, concrete roofing, felt, fibre cement, corrugated iron, asphalt and wood against water attack.

**Benefits**

- Fast drying.
- For use on most common building surfaces.

**Areas For Use**

BLACK BITUMEN PAINT provides an effective waterproof, weatherproof, corrosion resistant protective coating. It is resistant to low concentrations of alkalis and acids and can withstand prolonged oxidation. It is suitable for application to a wide variety of materials including iron and steel, lead, zinc, aluminium, asbestos - cement, concrete, stone, wood, felt and brick and is mainly used for:

- Metal protection - corrugated iron sheets, fire escapes, stairways, ladders, storage tanks, gutters, down pipes, fences, railings, gates etc.
- As a protective coating for concrete structures, stone, brick, concrete screeds and sand/cement surfaces.
- Overcoating felt/wood.

**Limitations**

- Do not use in areas where subsequent solvent contact is likely.
- Do not use for potable drinking water tanks.
- Avoid inhalation of vapours in confined spaces.
- Allow sufficient drying time between coats.
- Bitumen Paint may bleed through any paints subsequently applied over it. Apply a primer recommended by the paint manufacturer before overpainting.

**Surface Preparation**

As with all surface coatings, preparation of the surface is of great importance and will influence the degree of adhesion obtained and the life of the coating. All surfaces must be sound, stable and thoroughly clean and dry. Metal surfaces should be wire brushed to remove rust. Where long term protection is required an initial treatment of a rust inhibitive product such as red lead or zinc phosphate should be used. Loose or blistered paint should be removed as should tar based paint systems. New galvanised surfaces should be roughened with a wire brush or treated with a proprietary etch primer. Porous surfaces should be primed with EVERBUILD BITUMEN PRIMER

**Application**

EVERBUILD BLACK BITUMEN PAINT is ready for use and should not be thinned. Apply by brush or spray .

A minimum of two coats of Bitumen Paint should be applied, the first been allowed to dry (normally 2-4 hours depending on weather conditions) before the second is applied.

**PROTECTIVE COATING ON CONCRETE ETC**

Since concrete and some stone surfaces may be porous, an initial primer coat of EVERBUILD BITUMEN PRIMER should be applied.

**CLEANING TOOLS**

Tools may be cleaned by using white spirit. Spillage's should be wiped off surfaces before the bitumen paint has set.

**Specific Data**

<b>Type Of Solvent</b>	White spirits
<b>Flashpoint</b>	40°C
<b>Specific Gravity @ 20°C</b>	0.9
<b>Viscosity @ 20°C</b>	700-1200cps
<b>Coverage</b>	4 – 6m <sup>2</sup> per litre depending on porosity of substrate 11m <sup>2</sup> per litre on non porous surfaces
<b>Drying Time</b>	4-6 hours depending on drying conditions
<b>Service Temps</b>	-20 to +50°C
<b>Application Temps</b>	5-50°C. Surfaces must be free from ice and water
<b>Film Thickness Per Coat @ 11m<sup>2</sup> / Ltr</b>	Wet – 0.1mm Dry – 0.05mm
<b>Chemical And Water Resistance</b>	Resistant to: most salt solutions, dilute acids and alkalis, water and alcohol. Not resistant to: oils, solvents and some detergent solutions

**Health & Safety**

Consult MSDS for full list of hazards.

**Storage**

EVERBUILD BLACK BITUMEN PAINT contains a flammable solvent, and all normal precautions against fire must be taken during both storage and use. Store in original container in cool dry conditions. Keep away from sources of ignition.

### **Shelf Life**

24 months from date of manufacture in tightly sealed, undamaged containers.

*The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.*