



Specialist Construction Supplies for Repair, Maintenance, Building & Infrastructure

Formstrike MRO Data Sheet

Specification notes

Product: **Formstrike MRO**

Supplier:

Arcon Construction Supplies
19-20 Prestwood Court
Leacroft Road
Warrington
WA3 6SB

Tel: **01925 852225**

Email: mail@arconsupplies.co.uk

Web: www.arconsupplies.co.uk

Call 01925852225 or visit [Arcon Construction Supplies](http://www.arconconstruction.com) website

...for technical, specification & application advice;

or

...for more information on our other repair, maintenance,
engineering and construction specialist products.

[Industrial Flooring](#) | [Concrete Repairs](#) | [Protective and Waterproof Coatings](#)

[Jointing and Paving Mortars](#) | [Anti-slip Floor Paints](#) | [Non-shrink Grouts & Mortars](#)

Formstrike MRO Data Sheet

Formstrike MRO

Concrete Release Agent

Description

A versatile neat oil with surfactant which is designed to give optimum release and surface finish for a wide range of formwork materials. Complies with the British Cement Association, Category 2.

Advantages

- Produces a uniform stain free concrete surface.
- Effects a positive release hence reducing cleaning time.
- Protects both metal and timber forms.
- Economical in use and easily applied.

Technical Information

Appearance	Low Viscosity Amber Liquid
Specific Gravity at 20°C	0.84
Viscosity	13 Cps
Saponification value	3.0
Freezing Point	-25°C
Coverage	15-30 m ² per litre

Application Instructions

1. The form surface should be clean prior to application of the mould oil.
2. A thin even film should be applied preferably by spray, though brush or rollers may be used. Excess material should not be allowed to collect in the bottom of the moulds.
3. New unsealed timber requires a double application prior to the first cast.

Packaging

Formstrike MRO is available in 20 litre and 210 litre drums and in 1000 litre bulk tanks.

Storage

Mould Oils should be stored at normal temperature, out of the reach of children and away from foodstuffs.

Health & Safety

Gloves and goggles should be worn when using this product. Accidental splashes on skin should be removed by washing with soap and water.

Contact with eyes should be avoided and accidental contamination should be washed out and medical attention sought. If swallowed, do not induce vomiting and seek medical aid.

Ensure adequate ventilation and do not use near naked flames or smoke during use as this product is flammable.

Technical Note

Formstrike MRO, when used in accordance with the manufacturers recommendations, does not cause staining. Concrete 'staining' can be caused by a number of factors on which our Technical Department can advise.

Technical Support

Through our technical department and laboratories we can offer a comprehensive service to specifiers and contractors. Technical representatives are available to provide further information and arrange demonstrations.

