



Specialist Construction Supplies for Repair, Maintenance, Building & Infrastructure

## MMA Linemark Data Sheet

### Specification notes

Product: **MMA Linemark**

Supplier:

**Arcon Construction Supplies**  
**19-20 Prestwood Court**  
**Leacroft Road**  
**Warrington**  
**WA3 6SB**

Tel: **01925 852225**

Email: [mail@arconsupplies.co.uk](mailto:mail@arconsupplies.co.uk)

Web: [www.arconsupplies.co.uk](http://www.arconsupplies.co.uk)

Call 01925852225 or visit [Arcon Construction Supplies](http://www.arconconstruction.com) website

...for technical, specification & application advice;

or

...for more information on our other repair, maintenance,  
engineering and construction specialist products.

[Industrial Flooring](#) | [Concrete Repairs](#) | [Protective and Waterproof Coatings](#)

[Jointing and Paving Mortars](#) | [Anti-slip Floor Paints](#) | [Non-shrink Grouts &](#)

[Mortars](#)

**MMA Linemark Data Sheet**

## MMA Linemark

### Methacrylate Line Marking Paint

#### Description

MMA Linemark is a methacrylate based line marking paint designed for application to a wide range of surfaces, offering excellent colour stability, it is both hard wearing and chemically resistant with an inherent long-term flexibility. MMA Linemark is available in three different grades;

Standard - designed for external applications with heavy traffic.

Reflective - designed for external application with heavy traffic where greater visibility of demarcations is required.

Smooth - designed for internal applications or for light trafficked areas.

#### Advantages

- Available in standard and high luminescence grades.
- Easy application.
- Quick drying, can be trafficked within 1 hour.
- Excellent UV/colour stability.
- Very good adhesion to most substrates.
- Inherent flexibility provides excellent ductility.

#### Technical Information

Viscosity	15,000cps
S.G.	1.95
Coverage	0.3m <sup>2</sup> - 0.5m <sup>2</sup> per Kilo
Colours available	White/Yellow
Min. application temp.	-5°C
Max. application temp.	30°C
Flash point	10°C
Gel Time	Approx. 30 minutes

#### Surface Preparation

Ensure the surface is reasonably clean and dry. Damaged and worn areas should be repaired prior to application.

#### Mixing

Linemark only requires the addition of the powder accelerator after which it should be stirred thoroughly prior to use. It is advised that the mixing be performed using a slow speed mechanical mixer and suitable paddle. Mix for at least two minutes ensuring no unmixed material remains on the sides of the tin.

#### Application Instructions

Application is made by either brush, roller or by mechanical former.

#### Limitations

Linemark is not recommended for coating composition tiles and other plastic floor coverings. Please contact Nufins technical department prior to application.

#### Packaging

Linemark is available in 8 kg composite units.

#### Health & Safety

Adequate ventilation should be provided and all naked flames extinguished during application. Do not smoke during application. The use of gloves and a suitable barrier cream is advised.

#### Storage

When stored unopened at normal room temperature the shelf life is 6 months. Keep out of reach of children.



## Technical Support

Through our technical department and laboratories we can offer a comprehensive service to specifiers and contractors. Technical representatives are available to provide further information and arrange demonstrations.

