



Specialist Construction Supplies for Repair, Maintenance, Building & Infrastructure

Resupatch

Specification notes

Product: **Resupatch**

Supplier:

Arcon Construction Supplies
19-20 Prestwood Court
Leacroft Road
Warrington
WA3 6SB

Tel: **01925 852225**

Email: mail@arconsupplies.co.uk

Web: www.arconsupplies.co.uk

Call 01925852225 or visit [Arcon Construction Supplies](http://www.arconsupplies.co.uk) website

...for technical, specification & application advice;

or

...for more information on our other repair, maintenance,
engineering and construction specialist products.

[Industrial Flooring](#) | [Concrete Repairs](#) | [Protective and Waterproof Coatings](#)

[Jointing and Paving Mortars](#) | [Anti-slip Floor Paints](#) | [Non-shrink Grouts & Mortars](#)

Resupatch



A **SHERWIN-WILLIAMS** Company



REF : PAST 2016 06

Resupatch

DESCRIPTION

Resupatch is a two-pack easy to use epoxy resin mortar, with excellent mechanical properties. This makes it ideal for rapid repair of concrete surfaces in heavy duty environments.

Resupatch FH is also available as a fast-cure mortar for same day repairs which can be overlaid in 4 hours at 20°C.

ADVANTAGES

- Low odour, safe for to install in Food Production areas
- Hard wearing durable repairs for Industrial Use
- Ease of application
- Minimum surface preparation
- Can be feather edged
- Excellent abrasion and impact resistance
- Concrete like in appearance
- Dust-free & permanent

RECOMMENDED USES

- Any sound concrete requiring repairs
- Warehouse areas
- Chemical production and storage
- Printing and packaging areas
- Engineering facilities
- Automotive industry
- Aerospace production areas
- Industrial workshops

PRODUCT INFORMATION

System thickness (dry)	Solids content	Pack sizes	Pack make up	Shelf life	Storage
As Required	100%	5 Kg. & 20 Kg.	5 kg. unit - 1 X Base/Aggregate Blend 1 X Hardener 20 kg. unit - 1 X Base/Aggregate Blend 1 X Hardener	12 Months (Base & Hardener)	Keep out of direct Sunlight. Store in a dry place, not below 15°C

DRYING TIMES & COVERAGE RATES at 20°C

Coverage rate	Pot life	Recoat time	Light traffic	Full traffic	Full chemical cure
5 kg. has a 2.5 Litre. volume 20 kg. has a 10 Litre volume	Including Aggregate (30 Mins)	For Seal Coats 12 - 16 Hours (4 Hours if using Resupatch FH)	24 Hours	72 Hours	Up to 7 Days



