



REF : PEWC 2013 12

Resupen WB Wall

DESCRIPTION

Resupen WB wall is a coloured UV stable polyurethane finish for application onto vertical surfaces such as concrete, plaster and wood.

Grades Available : - Resupen WB Std - for a satin finish
 Resupen WB Matt - for a matt finish

ADVANTAGES

- UV stable finish
- Good abrasion & impact resistance
- Resistant to hot water
- Good chemical resistance
- Hygienic
- No VOC's

RECOMMENDED USES

- Food and Beverage industry
- Pharmaceutical & healthcare areas
- Laboratories
- Clean rooms
- As a wall finish seal coat onto prepared existing coatings

PRODUCT INFORMATION

System thickness (dry)	Solids content by weight	Pack sizes	Pack make up	Shelf life	Storage
40 microns	38%	5 Litre	1 X Base 1 X Hardener	12 Months (Base & Hardener)	Keep out of direct sunlight. Store in a dry Place

DRYING TIMES & COVERAGE RATES at 20°C

Coverage rate	Pot life	Recoat time	Light Traffic	Full Traffic	Full chemical cure
Standard : 5 litres will cover 40 sq m Matt : 5 litres will cover 40 sq m	1-2 Hours	6 - 8 Hours	12-16 Hours	48 Hours	Up to 7 Days



BRITISH COATINGS FEDERATION



www.resinsurfaces.co.uk

