



Specialist Construction Supplies for Repair, Maintenance, Building & Infrastructure

Ultracrete SCJ Spray Data Sheet

Specification notes

Product: **Ultracrete SCJ Spray**

Supplier:

Arcon Construction Supplies
19-20 Prestwood Court
Leacroft Road
Warrington
WA3 6SB

Tel: **01925 852225**

Email: mail@arconsupplies.co.uk

Web: www.arconsupplies.co.uk

Call 01925852225 or visit [Arcon Construction Supplies](http://www.arconsupplies.co.uk) website

...for technical, specification & application advice;

or

...for more information on our other repair, maintenance,
engineering and construction specialist products.

[Industrial Flooring](#) | [Concrete Repairs](#) | [Protective and Waterproof Coatings](#)

[Jointing and Paving Mortars](#) | [Anti-slip Floor Paints](#) | [Non-shrink Grouts &](#)

[Mortars](#)

Ultracrete SCJ Spray Data Sheet

SCJ

Seal and Tack Coat Spray

ULTRA CRETE

Cold Lay Asphalt Concretes



A cold joint sealer that is applied onto vertical edges and surface base before the application of asphalt.

- HAPAS Approved since 2005
- Prevents water ingress
- Improves bond
- Prolongs the life of your repair
- Can be used in all weathers

Applications

SCJ is a bitumen cold joint sealer & tack coat spray that is applied onto vertical edges and the surface base before the application of asphalt. It will increase the bond of the material to the substrate and waterproof the area. This will significantly enhance the reinstatement's performance by preventing the ingress of water and freeze/thaw effect.

Technical

SCJ is supplied in 750ml spray cans, with the bitumen being discharged by inverting the container and pressing the spray button.

Preparation

Remove as much standing water and loose particles as possible prior to product application. The sealer can be applied to damp or dry surfaces.

Application

Hold the can tightly and shake vigorously before use. Invert the can and press the spray button. Cover the area to be sealed with long strokes from a distance of 175mm to 250mm, working from the top downwards. Ensure that the entire surface is covered.

Cleaning

Point nozzle upward immediately after use and spray for a few seconds to clear it, taking care not to spray into wind. Failure to clean the nozzle after use could result in the aerosol becoming blocked rendering the product unusable.

Storage

Aerosol cans must NOT be exposed to direct sunlight or temperatures above 50°C. Store in a cool well-ventilated place.

Shelf life

Shelf life in correct conditions for sealed goods is 12 months.

Health, Safety and Environmental

Please ensure that appropriate PPE is used when preparing, mixing and applying products. Always wash your hands before consuming food and make sure that materials are kept safely out of reach of children and animals. Please dispose of packaging and waste responsibly and in accordance with local authority requirements. A full material datasheet relating to this product is available from instarmac.co.uk.

Quality assurance

All products are manufactured in a plant whose quality management system is certified / registered as being in conformity with BS EN ISO 9001, 14001, and OHSAS 18001. Our products are guaranteed against defective materials and manufacture, and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept any liability arising from the application or use of our products because we have no direct or continuous control over where and how our products are used. All products are sold subject to our conditions of sale, copies of which may be obtained on request.



compliance
number: 2314



Technical data

Colour	black
Unit/packaging	750ml can, 12 cans per box

Contact Us

Instarmac® Group plc, Birch Coppice Business Park, Danny Morson Way, Dordon, Tamworth, Staffordshire, B78 1SE, United Kingdom

Tel: +44 (0) 1827 872244 Fax: +44 (0) 1827 874466

Email: email@instarmac.co.uk Order: orders@instarmac.co.uk Website: instarmac.co.uk

Vers5.07.2015 Information correct at time of print