



REF : RSFO 2011 05

# Resufloor 2000

## DESCRIPTION

Resufloor 2000 is a self-smoothing epoxy resin seamless floor finish designed to provide a flat hard wearing gloss finish 2 - 3 mm in thickness following the profile of the existing floor.

The system gives aesthetically pleasing results with chemical resistance and durability.

## ADVANTAGES

- Seamless
- Hard wearing durable floor for industrial use
- Ease of application
- Hygienic
- Decorative - available in an attractive range of colours
- Excellent abrasion and impact resistance
- Good chemical resistance
- Smooth finish for precise operating equipment

## RECOMMENDED USES

- Pharmaceutical production
- Printing and packaging areas
- Television studios
- Automotive production
- Nightclubs
- Domestic studios
- Industrial workshops

## PRODUCT INFORMATION

System Thickness (dry)	Solids Content	Pack Size	Pack Make Up	Shelf life	Storage
2 mm to 3 mm	100%	14 kg. & 28 kg.	14 kg. - 1 X Base 1 X Hardener 1 X Aggregate bag  28 kg. - as above, 2 X Aggregate bag	12 Months (Base & Hardener) 12 Months (Aggregate)	Keep out of direct Sunlight. Store in a Dry Place

## DRYING TIMES & COVERAGE RATES at 20 ° C

Coverage rate	Pot life	Recoat time	Light traffic	Full traffic	Full chemical cure
7.5 sq m per 28 kg. unit @ 2mm thickness	Including Aggregate 30 Mins	For non-slip seal coats 12-16 Hours (Depending on Temperature)	24 Hours	72 Hours	7 Days



[www.resinsurfaces.co.uk](http://www.resinsurfaces.co.uk)

