



Specialist Construction Supplies for Repair, Maintenance, Building & Infrastructure

Masterflow 885 Safety Data Sheet

Safety Data Sheet

Product: **Masterflow 885**

Supplier:

Arcon Construction Supplies

19-20 Prestwood Court

Leacroft Road

Warrington

WA3 6SB

Tel: **01925 852225**

Email: mail@arconsupplies.co.uk

Web: www.arconsupplies.co.uk

Call **01925 852225** or visit [Arcon Construction Supplies](http://www.arconconstruction.com)
... for more information on our flooring and construction products

[Industrial Flooring](#) | [Concrete Repairs](#) | [Protective and Waterproof Coatings](#)
[Jointing and Paving Mortars](#) | [Anti-slip Floor Paints](#) | [Concrete Repair Mortars](#)

SAFETY DATA SHEET

MASTERFLOW 885

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

PRODUCT NAME: MASTERFLOW 885

PART No.: F000088

SYNONYMS, TRADE NAMES: Embeco Grout

2 COMPOSITION/INFORMATION ON INGREDIENTS

| INGREDIENT NAME | EINECS No. | CAS No. | CONTENTS | SYMBOL | RISK (R No.) |
|-----------------|------------|------------|----------|--------|--------------|
| PORTLAND CEMENT | | 65997-15-1 | 30-60 % | Xi | 36/38, 41 |

The full text for all R-phrases are shown in section 16.

COMPOSITION COMMENTS: Mixture based on siliceaceous ferrous fillers portland cement

3 HAZARDS IDENTIFICATION

Irritating to skin.
Risk of serious damage to eyes.

4 FIRST AID MEASURES

INHALATION: Move the exposed person to fresh air at once. Provide fresh air, warmth and rest, preferably in a comfortable upright sitting position. Get medical attention if any discomfort continues.

INGESTION: DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Promptly get affected personnel to drink large volumes of water to dilute the swallowed chemical. Obtain medical advice. Provide rest, warmth and fresh air.

SKIN: Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if irritation develops.

EYES: Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: This material is not flammable. Use extinguishing media appropriate for surrounding fire.

6 ACCIDENTAL RELEASE MEASURES

PRECAUTIONS TO PROTECT ENVIRONMENT: Avoid subsoil penetration. Prevent product from entering drains. Do not contaminate surface water.

SPILL CLEANUP METHODS: Shovel into dry containers. Cover and move the containers. Flush the area with water. Wear necessary protective equipment. Minimise dust formation.

MASTERFLOW 885

7 HANDLING AND STORAGE

USAGE PRECAUTIONS: Avoid handling which leads to dust formation. Provide good ventilation.
STORAGE PRECAUTIONS: Store at moderate temperatures in dry, well ventilated area.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENT COMMENTS: Nuisance Dust 8 Hour TWA 10 Mg/M³ Inhalable 4 Mg/M³ Respirable

PROTECTIVE EQUIPMENT:



VENTILATION: Provide adequate general and local exhaust ventilation.

RESPIRATORS: Respiratory protection must be used if air concentration exceeds acceptable level. Dust filter P2 (for fine dust).

PROTECTIVE GLOVES: No specific hand protection noted, but gloves may still be advisable. For prolonged or repeated skin contact use suitable protective gloves. Rubber or plastic.

EYE PROTECTION: Wear dust resistant safety goggles where there is danger of eye contact.

OTHER PROTECTION: Wear appropriate clothing to prevent repeated or prolonged skin contact. Wet cement burns are painless, prevention of contact with skin is vital. Provide eyewash station.

HYGIENIC WORK ROUTINES: Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. No eating or drinking while working with this material. **DO NOT SMOKE IN WORK AREA!**

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Powder, dust. **COLOUR:** Grey.
ODOUR/TASTE: None
SOLUBILITY DESCRIPTION: Insoluble in water.

10 STABILITY AND REACTIVITY

STABILITY: Normally stable.

CONDITIONS TO AVOID: Not known.

MATERIALS TO AVOID: Strong oxidizing agents. Strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS:

Fire or high temperatures create: Asphyxiating gases/vapours/fumes of: Carbon dioxide (CO₂). Carbon monoxide (CO).

11 TOXICOLOGICAL INFORMATION

INHALATION: Dust may irritate respiratory system or lungs.

INGESTION: May cause discomfort if swallowed.

SKIN: Powder may irritate skin.

EYES: Particles in the eyes may cause irritation and smarting. Risk of serious eye damage

HEALTH WARNINGS: Cement contains chromium VI which may cause sensitisation in select individuals

TARGET ORGANS: Skin. Eyes. Respiratory system, lungs.

MASTERFLOW 885**12 ECOLOGICAL INFORMATION**

ENVIRONMENTAL HAZARDS: Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS: Recover and reclaim or recycle, if practical. Dispose of on site landfill area. Dispose of in accordance with Local Authority requirements.

14 TRANSPORT INFORMATION

ROAD:
ROAD TRANSPORT NOTES: Not classified for road transport.

RAIL:
RAIL TRANSPORT NOTES: Not classified for rail transport.

SEA:
AIR:
AIR TRANSPORT NOTES: Not classified for air transport.

15 REGULATORY INFORMATION**LABEL FOR SUPPLY:****IRRITANT**

RISK PHRASES: R-38 Irritating to skin.
R-41 Risk of serious damage to eyes.

SAFETY PHRASES: S-24/25 Avoid contact with skin and eyes.
S-26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S-39 Wear eye/face protection.
S-60 This material and its container must be disposed of as hazardous waste.
U-3 Contact with wet cement may cause irritation, dermatitis or burns.
U-4 Contact between cement powder and body fluids (eg sweat and eye fluid) may also cause irritation, dermatitis or burns.
U-6 Contains chromium (VI). May produce an allergic reaction

UK ENVIRONMENTAL LISTINGS: Rivers (Prevention of Pollution) Act 1961.
Control of Pollution (Special Waste Regulations) Act 1980.

EC DIRECTIVES: System of specific information relating to Dangerous Preparations. 91\155.
STATUTORY INSTRUMENTS: Chemicals (Hazard Information and Packaging) Regulations.
APPROVED CODE OF PRACTICE: Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES: Occupational Exposure Limits EH40.
Introduction to Local Exhaust Ventilation HS(G)37.
CHIP for everyone HSG(108).



The Chemical Company

MASTERFLOW 885

16 OTHER INFORMATION

| | | |
|---|---|---------------------------------|
| INFORMATION SOURCES: | Dangerous Properties of Industrial Materials Report, N.Sax et.al. | |
| REVISION DATE: | 01/10/01 | |
| REVISION No. /REPLACES SDS ISSUED: | Issue 1 | |
| SDS No.: | SDS0112 | |
| R-PHRASES (Full Text): | R-41 | Risk of serious damage to eyes. |
| | R-36/38 | Irritating to eyes and skin. |