



Specialist Construction Supplies for Repair, Maintenance, Building & Infrastructure

## MMA Linemark Technical Data Sheet

### Specification notes

Product: **MMA Linemark**

Supplier:

**Arcon Construction Supplies**  
**19-20 Prestwood Court**  
**Leacroft Road**  
**Warrington**  
**WA3 6SB**

Tel: **01925 852225**

Email: [mail@arconsupplies.co.uk](mailto:mail@arconsupplies.co.uk)

Web: [www.arconsupplies.co.uk](http://www.arconsupplies.co.uk)

Call 01925852225 or visit [Arcon Construction Supplies](http://www.arconconstruction.com) website

...for technical, specification & application advice;

or

...for more information on our other repair, maintenance,  
engineering and construction specialist products.

[Industrial Flooring](#) | [Concrete Repairs](#) | [Protective and Waterproof Coatings](#)

[Jointing and Paving Mortars](#) | [Anti-slip Floor Paints](#) | [Non-shrink Grouts &](#)

[Mortars](#)

**MMA Linemark Technical Data Sheet**

## MMA Linemark

### Methacrylate Line Marking Paint

#### Description

MMA Linemark is a methacrylate based line marking paint designed for application to a wide range of surfaces, offering excellent colour stability, it is both hard wearing and chemically resistant with an inherent long-term flexibility. MMA Linemark is available in two different grades;

Standard - designed for external applications with heavy traffic.

Smooth - designed for internal applications or for light trafficked areas.

#### Advantages

- Available in standard and high luminescence grades
- Easy application
- Quick drying, can be trafficked within 1 hour
- Excellent UV/colour stability
- Very good adhesion to most substrates
- Inherent flexibility provides excellent ductility

#### Technical Information

Viscosity	Approx. 15,000cps
S.G.	2.1 Standard and Reflective 1.95 Smooth
Coverage	0.4m <sup>2</sup> /kg @ 1mm Standard and Reflective 0.5m <sup>2</sup> /kg @ 1mm Smooth
Colours available	White/Yellow
Min. application temperature	-5°C
Max. application temperature	30°C
Flash point	10°C
Gel Time	10 minutes Standard and Reflective 20 minutes Smooth

#### Surface Preparation

Ensure the surface is clean and dry. Damaged and worn areas should be repaired prior to application.

#### Mixing

MMA Linemark requires the addition of the powder accelerator. Mix thoroughly prior to use. Mixing should be performed using a slow speed mechanical mixer and suitable paddle. Mix for at least two minutes ensuring no unmixed material remains on the sides of the mixing vessel.

#### Application Instructions

Application is made by either brush, roller, trowel or by mechanical former depending on grade.

#### Limitations

Linemark is not recommended for coating composition tiles and other plastic floor coverings. Please contact Nufins technical department prior to application.

#### Packaging

Linemark is available in 5 kg composite units.

#### Storage

MMA Linemark is flammable (flash point is 10°C), due precautions should be made when handling and storing this material.

The shelf life is 6 months when stored unopened in dry, normal conditions and away from direct sunlight. Protect from frost.



## Health & Safety

Product Safety Data Sheets (SDS) are available from Nufins. SDS sheets are provided to help customers satisfy their safe handling, use and disposal needs as well as assist with any conformance requirements made locally by health and safety regulations.

SDS are continually updated to provide the latest information to our customers. We therefore recommend contacting our head office to obtain the most recent and accurate SDS before handling and using any product.

## Disclaimer

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied themselves independently as to the suitability of our products for their own particular purpose. In no event shall Nufins be liable for consequential or incidental damages.

Users must always refer to the most recent issue of the Technical Datasheets, copies of which will be supplied on request.

## Technical Support

Through our technical department and laboratories we can offer a comprehensive service to specifiers and contractors. Technical contacts are available to provide further information and arrange demonstrations.