



Specialist Construction Supplies for Repair, Maintenance, Building & Infrastructure

Nuproof Data Sheet

Specification notes

Product: **Nuproof**

Supplier:

Arcon Construction Supplies

19-20 Prestwood Court

Leacroft Road

Warrington

WA3 6SB

Tel: **01925 852225**

Email: mail@arconsupplies.co.uk

Web: www.arconsupplies.co.uk

Call **01925 852225** or visit [Arcon Construction Supplies](http://www.arconconstruction.com)
... for more information on our flooring and construction products

[Industrial Flooring](#) | [Concrete Repairs](#) | [Protective and Waterproof Coatings](#)
[Jointing and Paving Mortars](#) | [Anti-slip Floor Paints](#) | [Concrete Repair Mortars](#)



Nuproof

Waterproofing Coating



Nufins

Description

Nuproof is a water based, latex modified bitumen emulsion with in-built flexibility and excellent adhesion. It provides a tough durable film which waterproofs and protects most building surfaces.

Standard Compliance

ASTM D2939-03.

Advantages

- Excellent adhesion and low permeability.
- In-built flexibility
- Reduced susceptibility to extremes of temperature.
- Tough film resistant to rupture during back filling.

Applications

- Waterproof coating for bridge abutments prior to back filling.
- As a damp-proof membrane under concrete and roof screeds.
- As a damp-proof membrane for internal walls subject to rising damp.
- Repairs to cracks in blacktop surfacing and concrete.
- To waterproof and repair defective concrete and asphalt roofs.

Technical Information

Colour:	Black
Type:	A blend of bitumen emulsion and rubber latex.
Touch Dry:	3-6 Hours
Viscosity:	6000 cps
S.G. at 20°C:	1.0
Solids Content:	50%
Application Temp.:	5-35°C
Application Rate:	2m ² per Litre per Coat.

Surface Preparation

All surfaces should be sound and free from dust, dirt and grease. Excessively dry porous surfaces should be dampened down to assist application and maintain the correct coverage. When applied to green concrete, Nuproof will act as a curing membrane to assist hydration of the cement. Application should not be carried out in frosty weather or when rain is expected.

Application Instructions

The normal method of application is to use a soft brush which should be dampened with water before use. On hot, dry or very absorbent surfaces it is suggested that the surface is dampened down or primed using a coat of Nuproof, diluted with 1 part water to 5 parts Nuproof. Nuproof should be applied in two coats at right angles to one another, the second coat being applied after the first coat has thoroughly dried.

Waterproof Coating For Concrete

As above.

Crack Repairs In Blacktop Or Concrete

Fine cracks may be repaired using Nuproof neat. Cracks up to 6mm may be filled using Nuproof mixed with a fine sand in a ratio of 2:1 by volume. Large cracks over 6mm should be filled with a similar mixture plus the addition of Portland cement. Repairs should be blinded with fine sand to facilitate early trafficking. Large repairs may need topping up after 24 hours.

Waterproofing Walls And Use As A Keying Treatment

Internal walls may be treated with Nuproof to provide a waterproof membrane and a key for subsequent plastering. Nuproof should be applied to the clean surface and allowed to dry, a second coat is then applied at right angles to the first coat and blinded with sharp sand whilst the coat is still wet. This coat should be allowed to dry for at least 24 hours before plastering.

Immediately after use all equipment should be washed in a solution of soap flakes and water (not detergent).

Brushes should be kept soaked between working periods and any excess water removed before use.

Packaging

Nuproof is available in 5, 25 and 200 litre containers.

Storage

Store under cover between 5-40°C. Protect from frost.

Health & Safety

Is non-flammable but protective clothing should be worn to avoid skin contact. Splashes should be removed from the skin with soap and water before the material has dried.

Limitations

Work should not proceed in wet or frosty conditions or when rain is expected.

Do not apply when the temperature is below 5°C.

Technical Support

Through our technical department and laboratories we can offer a comprehensive service to specifiers and contractors.

Technical representatives are available to provide further information and arrange demonstrations.



Kingston House, 3 Walton Road, Pattinson North, Washington, Tyne & Wear, NE38 8QA, United Kingdom

T: +44(0) 191 416 8360

F: +44(0) 191 415 5966

W: www.nufins.com

E: info@usluk.com

This information and/or specification contained herein or in our literature or given by Nufins, its employees, distributors, agents or representatives with regard to its product or their use or application are given in good faith, but no liability is accepted for any loss or damage (including direct or consequential loss or loss of profits) from the use of products because Nufins has no control over how its products are used and applied.

