

Polysolv

Polystyrene Dissolver

Description

A powerful solvent blend for dissolving of expanded polystyrene.

Advantages

- Excellent searching and penetrative properties.
- Ready for use, easily applied to vertical surfaces.
- Easily dissolves expanded polystyrene formers, making voids/boxouts ready for re-concreting.
- Not classified as flammable.

Technical Information

Type	Aromatic Hydrocarbon Solvent
Specific gravity	0.91
Flash point	62°C
Boiling point	180-285°C

Application

Polysolv should be applied undiluted on to the expanded polystyrene and allowed to dissolve the polystyrene for several minutes. The residues should then be wiped off or flushed away with water. Measures should be taken to ensure that the Polysolv does not enter any drainage systems.

Coverage: approximately 40 litres of Polysolv is sufficient to dissolve 1m³ of polystyrene.

Packaging

Polysolv is available in 5 and 20 litre containers.

Storage

Polysolv should be stored in a cool, well ventilated location away from foodstuffs and out of the reach of children.

Health & Safety

Goggles and gloves should be worn. If using in confined spaces provide adequate ventilation.

Technical Support

Through our technical department and laboratories we can offer a comprehensive service to specifiers and contractors. Technical representatives are available to provide further information and arrange demonstrations.

