



Specialist Construction Supplies for Repair, Maintenance, Building & Infrastructure

Ultra DPM IT 2 coat Safety Data Sheet

Safety Data Sheet

Product: **Ultra DPM IT 2 coat**

Supplier:

Arcon Construction Supplies

19-20 Prestwood Court

Leacroft Road

Warrington

WA3 6SB

Tel: **01925 852225**

Email: mail@arconsupplies.co.uk

Web: www.arconsupplies.co.uk

Call **01925 852225** or visit [Arcon Construction Supplies](http://www.arconconstruction.com)
... for more information on our flooring and construction products

[Industrial Flooring](#) | [Concrete Repairs](#) | [Protective and Waterproof Coatings](#)
[Jointing and Paving Mortars](#) | [Anti-slip Floor Paints](#) | [Concrete Repair Mortars](#)



SAFETY DATA SHEET ULTRA DPM IT 2 COAT HARDENER

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME ULTRA DPM IT 2 COAT HARDENER
APPLICATION Two Component Damp Proof Membrane System
SUPPLIER Instarmac Group plc
Danny Morson Way
Birch Coppice Business Park
Dordon, Tamworth
Staffordshire. B78 1SE
United Kingdom
Tel: +44 (0) 1827 872244
Fax: +44 (0) 1827 874466
email@instarmac.co.uk
www.instarmac.co.uk
EMERGENCY TELEPHONE +44 (0)7971 217 347

2 HAZARDS IDENTIFICATION

Causes burns. May cause sensitisation by skin contact. Harmful by inhalation, in contact with skin and if swallowed.

CLASSIFICATION Xn;R20/21/22. C;R34. R43.

3 COMPOSITION/INFORMATION ON INGREDIENTS

| Name | EC No. | CAS-No. | Content | Classification |
|---------------------------------------|-----------|------------|---------|------------------------------|
| 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL | 202-013-9 | 90-72-2 | 1-10% | Xn;R22 Xi;R36/38 |
| 3-AMINOPROPYLTRIETHOXYSILANE | 213-048-4 | 919-30-2 | 1-10% | C;R34 Xn;R22 |
| BENZYL ALCOHOL | 202-859-9 | 100-51-6 | 30-60% | Xn;R20/22 |
| BIS(DIMETHYLAMINOMETHYL)-PHENOL | | 71074-89-0 | 1-10% | C;R34. |
| ISOPHORONEDIAMINE | 220-666-8 | 2855-13-2 | 10-30% | C;R34 Xn;R21/22 R43 R52/53 |
| SALICYLIC ACID | 200-712-3 | 69-72-7 | 1-10% | Xn;R20/21/22. Xi;R37/38,R41. |

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

Rinse mouth thoroughly. Drink plenty of water. Do not induce vomiting. Get medical attention immediately!

SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Immediately rinse with water. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Extinguish with foam, carbon dioxide or dry powder. Do not use water jet as an extinguisher, as this will spread the fire.

ULTRA DPM IT 2 COAT HARDENER

SPECIFIC HAZARDS

Toxic gases/vapours/fumes of Oxides of: Carbon. Nitrogen.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Avoid contact with skin and eyes. Provide adequate ventilation. Use protective gloves, goggles and suitable protective clothing.

ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses. Avoid discharge onto the ground. Contain spillages with sand, earth or any suitable adsorbent material.

SPILL CLEAN UP METHODS

Absorb with sand or other inert absorbent. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid contact with skin and eyes. Provide good ventilation. Observe good industrial hygiene practices. Do not eat, drink or smoke when using the product.

STORAGE PRECAUTIONS

Keep separate from food, feedstuffs, fertilisers and other sensitive material. Store in a cool and well-ventilated place. Store in closed original container at temperatures between 5°C and 25°C.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

In case of inadequate ventilation use suitable respirator.

HAND PROTECTION

Protective gloves must be used if there is a risk of direct contact or splash. Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

OTHER PROTECTION

Wear suitable protective clothing as protection against splashing or contamination.

HYGIENE MEASURES

Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Wash contaminated clothing before reuse.

9 PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|------------------|-----------------------|-----------|----------------------------|
| APPEARANCE | Liquid | | |
| COLOUR | Amber | | |
| ODOUR | Slight odour Ammonia | | |
| RELATIVE DENSITY | 0.98 - 1.04 approx 20 | VISCOSITY | 3000 - 3500 cps @ 23 deg C |

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

MATERIALS TO AVOID

Strong acids. Strong alkalis. Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

During fire, toxic gases (CO, CO₂, NO_x) are formed.

ULTRA DPM IT 2 COAT HARDENER

11 TOXICOLOGICAL INFORMATION

INHALATION

Harmful by inhalation.

INGESTION

May cause chemical burns in mouth, oesophagus and stomach.

SKIN CONTACT

Causes burns. May cause sensitisation by skin contact.

EYE CONTACT

May cause chemical eye burns.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Hazardous waste landfill in sealed containers.

14 TRANSPORT INFORMATION



| | | | |
|-----------------------------|--------------------------|-------------------------|--------------------------------|
| UK ROAD CLASS | 8 | | |
| PROPER SHIPPING NAME | CORROSIVE LIQUID, N.O.S. | | |
| UN NO. ROAD | 1760 | UK ROAD PACK GR. | III |
| ADR CLASS NO. | 8 | ADR CLASS | Class 8: Corrosive substances. |
| ADR PACK GROUP | III | HAZARD No. (ADR) | 80 |
| ADR LABEL NO. | 8 | HAZCHEM CODE | 2X |
| CEFIC TEC(R) NO. | 80GC9-II+III | RID CLASS NO. | 8 |
| RID PACK GROUP | III | UN NO. SEA | 1760 |
| IMDG CLASS | 8 | IMDG PACK GR. | III |
| EMS | F-A, S-B | MARINE POLLUTANT | No. |
| UN NO. AIR | 1760 | AIR CLASS | 8 |
| AIR PACK GR. | III | | |

15 REGULATORY INFORMATION

LABELLING



Corrosive



Harmful

CONTAINS

BENZYL ALCOHOL
ISOPHORONEDIAMINE
SALICYLIC ACID

ULTRA DPM IT 2 COAT HARDENER

RISK PHRASES

| | |
|-----------|---|
| R34 | Causes burns. |
| R43 | May cause sensitisation by skin contact. |
| R20/21/22 | Harmful by inhalation, in contact with skin and if swallowed. |

SAFETY PHRASES

| | |
|-----------|---|
| S24/25 | Avoid contact with skin and eyes. |
| S26 | In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. |
| S36/37/39 | Wear suitable protective clothing, gloves and eye/face protection. |
| S45 | In case of accident or if you feel unwell, seek medical advice immediately (show label where possible). |
| S51 | Use only in well-ventilated areas. |
| S60 | This material and its container must be disposed of as hazardous waste. |

16 OTHER INFORMATION

REVISION DATE 04/06/2008

REV. NO./REPL. SDS GENERATED 1

RISK PHRASES IN FULL

| | |
|-----------|---|
| R20/21/22 | Harmful by inhalation, in contact with skin and if swallowed. |
| R20/22 | Harmful by inhalation and if swallowed. |
| R21/22 | Harmful in contact with skin and if swallowed. |
| R22 | Harmful if swallowed. |
| R34 | Causes burns. |
| R36/38 | Irritating to eyes and skin. |
| R37/38 | Irritating to respiratory system and skin. |
| R41 | Risk of serious damage to eyes. |
| R43 | May cause sensitisation by skin contact. |
| R52/53 | Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |

DISCLAIMER

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.

All goods are supplied in accordance with Instarmac Group plc's general conditions of sale, copies of which may be obtained by telephoning sales on 01827 872244



SAFETY DATA SHEET ULTRA DPM IT 2 COAT RESIN

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

| | |
|----------------------------|--|
| PRODUCT NAME | ULTRA DPM IT 2 COAT RESIN |
| APPLICATION | Two Component Damp Proof Membrane System |
| SUPPLIER | Instarmac Group plc Danny Morson Way Birch Coppice Business Park Dordon, Tamworth Staffordshire. B78 1SE United Kingdom Tel: +44 (0) 1827 872244 Fax: +44 (0) 1827 874466 email@instarmac.co.uk www.instarmac.co.uk |
| EMERGENCY TELEPHONE | +44 (0)7971 217 347 |

2 HAZARDS IDENTIFICATION

May cause sensitisation by skin contact. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xi;R36/38. R43. N;R51/53.

3 COMPOSITION/INFORMATION ON INGREDIENTS

| Name | EC No. | CAS-No. | Content | Classification |
|---|-----------|------------|---------|--------------------------------------|
| BISPHENOL F-EPOXY RESIN | | 9003-36-5 | 10-30% | Xi;R36/38. N;R51/53. R43. |
| C13-C15 ALKYLGLYCIDYLETHER | | 68081-84-5 | 1-10% | Xi;R36/38. R43. |
| EPOXY RESIN (Number average MW <= 700) | 500-033-5 | 25068-38-6 | 30-60% | R43 Xi;R36/38 N;R51/53 |
| GLYCIDYLETHER OF C12-C14 ALCOHOLS | | 68609-97-2 | 1-10% | R43 Xi;R38 |
| METHANOL | 200-659-6 | 67-56-1 | < 1 % | F;R11 T;R23/24/25,R39/23/24/25 |
| Solvent Naphtha (Petroleum), Light Aromatic | 265-199-0 | 64742-95-6 | < 1 % | Xn;R20. Xi;R36/37/38. N;R51/53. R10. |
| XYLENE | 215-535-7 | 1330-20-7 | < 1 % | R10 Xn;R20/21 Xi;R38 |

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

Rinse mouth thoroughly. Drink plenty of water. Do not induce vomiting. Get medical attention immediately!

SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Immediately rinse with water. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

ULTRA DPM IT 2 COAT RESIN

EXTINGUISHING MEDIA

Extinguish with foam, carbon dioxide or dry powder. Do not use water jet as an extinguisher, as this will spread the fire.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Avoid contact with skin and eyes. Provide adequate ventilation. Use protective gloves, goggles and suitable protective clothing.

ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses. Avoid discharge onto the ground. Contain spillages with sand, earth or any suitable adsorbent material.

SPILL CLEAN UP METHODS

Absorb with sand or other inert absorbent. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid contact with skin and eyes. Provide good ventilation. Observe good industrial hygiene practices. Do not eat, drink or smoke when using the product.

STORAGE PRECAUTIONS

Keep separate from food, feedstuffs, fertilisers and other sensitive material. Store in a cool and well-ventilated place. Store in closed original container at temperatures between 5°C and 25°C.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

| Name | Std | LT - ppm | LT - mg/m3 | ST - ppm | ST - mg/m3 |
|---|-----|-------------|---------------|-------------|---------------|
| METHANOL | WEL | 200 ppm(Sk) | 266 mg/m3(Sk) | 250 ppm(Sk) | 333 mg/m3(Sk) |
| Solvent Naphtha (Petroleum), Light Aromatic | | | 150 | | |
| XYLENE | WEL | 50 ppm(Sk) | 220 mg/m3(Sk) | 100 ppm(Sk) | 441 mg/m3(Sk) |

ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

In case of inadequate ventilation use suitable respirator.

HAND PROTECTION

Protective gloves must be used if there is a risk of direct contact or splash. Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

OTHER PROTECTION

Wear suitable protective clothing as protection against splashing or contamination.

HYGIENE MEASURES

Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Wash contaminated clothing before reuse.

9 PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|------------------|-----------------------|-----------|----------------------------|
| APPEARANCE | Liquid | | |
| COLOUR | Red | | |
| ODOUR | Slight odour | | |
| RELATIVE DENSITY | 1.28 - 1.40 approx 20 | VISCOSITY | 2750 - 3750 cps @ 23 deg C |

10 STABILITY AND REACTIVITY

ULTRA DPM IT 2 COAT RESIN

STABILITY

Stable under normal temperature conditions and recommended use.

MATERIALS TO AVOID

Strong acids. Strong alkalis. Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

During fire, toxic gases (CO, CO₂) are formed.

11 TOXICOLOGICAL INFORMATION

INHALATION

When working extensively on big surfaces in small and badly ventilated rooms, vapours may develop in concentrations which may cause headache and irritation of the eyes and the respiratory system.

INGESTION

Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

SKIN CONTACT

Irritating to skin. May cause sensitisation by skin contact.

EYE CONTACT

Irritating and may cause redness and pain.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Hazardous waste landfill in sealed containers.

14 TRANSPORT INFORMATION



| | | | |
|-----------------------------|---|-------------------------|---|
| UK ROAD CLASS | 9 | | |
| PROPER SHIPPING NAME | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. | | |
| UN NO. ROAD | 3082 | UK ROAD PACK GR. | III |
| ADR CLASS NO. | 9 | ADR CLASS | Class 9: Miscellaneous dangerous substances and articles. |
| ADR PACK GROUP | III | HAZARD No. (ADR) | 90 |
| ADR LABEL NO. | 9 | HAZCHEM CODE | 3Z |
| CEFIC TEC(R) NO. | 90GM6-III | RID CLASS NO. | 9 |
| RID PACK GROUP | III | UN NO. SEA | 3082 |
| IMDG CLASS | 9 | IMDG PACK GR. | III |
| EMS | F-A, S-F | MARINE POLLUTANT | No. |
| UN NO. AIR | 3082 | AIR CLASS | 9 |
| AIR PACK GR. | III | | |

15 REGULATORY INFORMATION

ULTRA DPM IT 2 COAT RESIN

LABELLING



Irritant



Dangerous for the environment

CONTAINS

BISPHENOL F-EPOXY RESIN
C13-C15 ALKYLGLYCIDYLETHER
EPOXY RESIN (Number average MW <= 700)
GLYCIDYLETHER OF C12-C14 ALCOHOLS

RISK PHRASES

| | |
|--------|---|
| R43 | May cause sensitisation by skin contact. |
| R36/38 | Irritating to eyes and skin. |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |

SAFETY PHRASES

| | |
|-----------|---|
| S24/25 | Avoid contact with skin and eyes. |
| S26 | In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. |
| S36/37/39 | Wear suitable protective clothing, gloves and eye/face protection. |
| S60 | This material and its container must be disposed of as hazardous waste. |
| S61 | Avoid release to the environment. Refer to special instructions/safety data sheets. |
| P5 | Contains epoxy constituents. See information supplied by the manufacturer. |

16 OTHER INFORMATION

INFORMATION SOURCES

Health and Safety Executive Guidance Note EH40 (amended annually) Workplace Exposure Limits. (United Kingdom)

REVISION DATE 04/06/2008

REV. NO./REPL. SDS GENERATED 1

RISK PHRASES IN FULL

| | |
|--------------|---|
| R10 | Flammable. |
| R11 | Highly flammable. |
| R20 | Harmful by inhalation. |
| R20/21 | Harmful by inhalation and in contact with skin. |
| R23/24/25 | Toxic by inhalation, in contact with skin and if swallowed. |
| R36/37/38 | Irritating to eyes, respiratory system and skin. |
| R36/38 | Irritating to eyes and skin. |
| R38 | Irritating to skin. |
| R39/23/24/25 | Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed. |
| R43 | May cause sensitisation by skin contact. |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |

DISCLAIMER

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.

All goods are supplied in accordance with Instarmac Group plc's general conditions of sale, copies of which may be obtained by telephoning sales on 01827 872244