



Specialist Construction Supplies for Repair, Maintenance, Building & Infrastructure

## Ultrascape PaveJoint Data Sheet

### Specification notes

Product: **Ultrascape PaveJoint**

Supplier:

**Arcon Construction Supplies**  
**19-20 Prestwood Court**  
**Leacroft Road**  
**Warrington**  
**WA3 6SB**

Tel: **01925 852225**

Email: [mail@arconsupplies.co.uk](mailto:mail@arconsupplies.co.uk)

Web: [www.arconsupplies.co.uk](http://www.arconsupplies.co.uk)

Call **01925 852225** or visit [Arcon Construction Supplies](http://www.arconconstruction.com)  
... for more information on our flooring and construction products

[Industrial Flooring](#) | [Concrete Repairs](#) | [Protective and Waterproof Coatings](#)  
[Jointing and Paving Mortars](#) | [Anti-slip Floor Paints](#) | [Concrete Repair Mortars](#)

# PAVE JOINT

READY TO USE JOINTING COMPOUND FOR DRIVES, PATHS & PATIOS

## 3 Simple Steps to Perfect Joints!

1. Pour contents of tub over joints.
2. Sweep tub contents into joints. Every joint must be completely filled and excess material removed from the paving surface
3. Soak the joints using either a hose pipe set to spray or watering can and rose.

### Before Application:

Ensure joints are no less than 2mm wide at the narrowest point, and no greater than 25mm at the widest. All joints must have a minimum depth of 25mm.

Due to the nature of **PAVEJOINT** some setting of the contents will have occurred in the tub. It is important to mix the contents dry in the tub before application.

**DO NOT** pre-fill joints with sand. **PAVEJOINT** must be applied to full depth. **DO NOT** apply in wet or damp conditions - this can result in the balling of **PAVEJOINT** making it difficult to fill the joints satisfactorily. Staining is also possible in these conditions.

**PAVEJOINT**'s colour comes from natural aggregates and can give a different appearance alongside different coloured paving. Check the colour against your chosen paving by opening the tub next to it.

Paved areas, beds and joints must be well drained to avoid standing water in joints for long periods.

**PAVEJOINT** is unsuitable for use in long-term/permanent immersion in water, but will withstand wet-dry weather cycles.

Protect against rainfall until hardened, and do not apply in temperatures below 5°C. Curing time will depend on temperature - cold weather retards, warm weather accelerates.

**PAVEJOINT**'s full cure can take up to 28 days. It must be left for 28 days before power washing the area.



# PAVE JOINT

READY TO USE JOINTING COMPOUND FOR DRIVES, PATHS & PATIOS

## COVERAGE:

200x100x50mm with a 3mm Joint =  
Approximately 6m per 20kg tub of **PAVEJOINT**

450x450x25mm with a 10mm Joint =  
Approximately 12.5m per 20kg tub of **PAVEJOINT**

For more detailed coverage information, please visit  
[www.ultrascape.co.uk](http://www.ultrascape.co.uk) and use our free product  
calculator, or call us on +44(0)1827 871871


## SHELF LIFE:

From date of manufacture in sealed tubs is 12 months

## PACKAGING:

20kg buckets (40 buckets to a pallet, delivered  
shrink-wrapped)

## AVAILABLE IN:



BUFF



NATURAL

Print colours should be treated as such, and are merely  
indicative of true product colour.



INITIAL SET: 8 Hours\*

FINAL SET: 3 Days\*

FINAL CURE: 28 Days\*

\* Dependant on temperature

SUITABLE FOR BLOCK PAVING,  
SETTS, COBBLES & FLAGS

ULTRASCAPE is a brand of the Instarmac Group plc  
Birch Coppice Business Park, Danny Morson Way, Dordon, Tamworth, Staffordshire, B78 1SE, United Kingdom  
Tel: +44(0)1827 872244 Fax: +44(0)1827 874466  
Email: [email@instarmac.co.uk](mailto:email@instarmac.co.uk) Order: [orders@instarmac.co.uk](mailto:orders@instarmac.co.uk) [www.instarmac.co.uk](http://www.instarmac.co.uk)

Ultrascape products are guaranteed against defective materials and manufacture, and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot, however, accept any liability arising from the application or use of our products because we have no direct or continuous control over where and how our products are used. All products are sold subject to our conditions of sale, copies of which can be obtained upon request or downloaded from [www.instarmac.co.uk](http://www.instarmac.co.uk).

Vers1.03.2010. Information correct at time of print.

An **INSTARMAC** Brand